

SAFETY DATA SHEET

ESTELITE Σ QUICK

1. Identification

Product identifier

Product name ESTELITE Σ QUICK

Recommended use of the chemical and restrictions on use

Application Resin-based Dental Restorative Material. For dental professionals only.

Details of the supplier of the safety data sheet

Supplier Tokuyama Dental America, Inc.
740 Garden View CT., Suite 200 Encinitas,
CA 92024 U.S.A.
Tel: (877) 378 3548 (Toll-Free)
Tel: (760)942-7211
Fax: (760)942-7212

Contact Person <http://www.tokuyama-dental.com/tdc/contact.html>

Manufacturer Tokuyama Dental Corporation
38-9, Taitou 1-chome, Taitou-ku, Tokyo
110-0016, Japan
TEL: +81-3-3835-2261
FAX: +81-3-3835-2265

Emergency telephone number

Emergency telephone California Poison Control System - San Francisco Division
San Francisco General Hospital
Bldg 5 Rm 2A21, 1001 Potrero Ave, San Francisco
Emergency telephone number: 1 800 222 1222
E-mail address: coadmin@calpoison.org
<http://www.calpoison.org>

National Capital Poison Center
3201 New Mexico Ave, Ste 310, Washington DC
Emergency telephone number: 1 800 222 1222
Telephone number: +1 202 362 3867
Facsimile number: +1 202 362 8377
E-mail address: pc@poison.org
<http://www.poison.org>

2. Hazard(s) identification

Classification of the substance or mixture

OSHA Regulatory Status This Product is Hazardous under the OSHA Hazard Communication Standard.

Physical hazards Not Classified

Health hazards Skin Sens. 1 - H317

Environmental hazards Not Classified

Label elements

ESTELITE Σ QUICK

Pictogram



Signal word

Warning

Hazard statements

H317 May cause an allergic skin reaction.

Precautionary statements

P261 Avoid breathing dust.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P302+P352 If on skin: Wash with plenty of water.
 P321 Specific treatment (see medical advice on this label).
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P501 Dispose of contents/ container in accordance with local regulations.

Contains

2-PROPENOIC ACID, 2-METHYL-, (1-METHYLETHYLIDENE)BIS[4,1-PHENYLENEOXY(2-HYDROXY-3,1-PROPANEDIYL)] ESTER, TRIETHYLENE GLYCOL DIMETHACRYLATE, p-METHOXYPHENOL

3. Composition/information on ingredients

Mixtures

2-PROPENOIC ACID, 2-METHYL-, (1-METHYLETHYLIDENE)BIS[4,1-PHENYLENEOXY(2-HYDROXY-3,1-PROPANEDIYL)] ESTER CAS number: 1565-94-2	10-30%
--	--------

TRIETHYLENE GLYCOL DIMETHACRYLATE CAS number: 109-16-0	5-10%
---	-------

2,6-DI-tert-BUTYL-p-CRESOL CAS number: 128-37-0 M factor (Chronic) = 1	<1%
--	-----

p-METHOXYPHENOL CAS number: 150-76-5	<1%
---	-----

TITANIUM DIOXIDE CAS number: 13463-67-7	< 0.1%
--	--------

4. First-aid measures

Description of first aid measures

General information

Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Inhalation

Move affected person to fresh air at once.

Ingestion

Try to induce vomiting. Get medical attention if any discomfort continues.

Skin Contact

Wash skin thoroughly with soap and water.

ESTELITE Σ QUICK

Eye contact Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing.

Most important symptoms and effects, both acute and delayed

Skin contact Allergic rash.

Indication of immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam. Carbon dioxide or dry powder.

Special hazards arising from the substance or mixture

Specific hazards When heated and in case of fire, irritating vapors/gases may be formed.

Hazardous combustion products No known hazardous decomposition products.

Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapors.

Special protective equipment for firefighters Wear chemical protective suit.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions No specific recommendations.

Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

Reference to other sections For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions All handling should only take place in well-ventilated areas.

Conditions for safe storage, including any incompatibilities

Storage precautions Store in a cool and well-ventilated place. Store at temperatures between 0°C/25°F and 32°C/77°F. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid exposure to high temperatures or direct sunlight.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

ESTELITE Σ QUICK

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

2,6-DI-tert-BUTYL-p-CRESOL

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m³ inhalable fraction and vapor

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m³ inhalable fraction and vapor

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m³ inhalable fraction and vapor

A4, A4, A4

p-METHOXYPHENOL

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m³

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m³

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m³

TITANIUM DIOXIDE

Long-term exposure limit (8-hour TWA): ACGIH 10 mg/m³

Long-term exposure limit (8-hour TWA): ACGIH 10 mg/m³

Long-term exposure limit (8-hour TWA): ACGIH 10 mg/m³

A4, A4, A4

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust

Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

OSHA = Occupational Safety and Health Administration.

Exposure controls

Appropriate engineering controls	Provide adequate general and local exhaust ventilation.
Eye/face protection	The following protection should be worn: Chemical splash goggles.
Hand protection	Wear protective gloves.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of skin contact.
Hygiene measures	Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Paste
Color	Yellow-white
Odor	Not available.
Odor threshold	Not available.
pH	pH (concentrated solution): 7
Melting point	Not available.
Initial boiling point and range	Not available.

ESTELITE Σ QUICK

Flash point	Not available.
Evaporation rate	Not available.
Evaporation factor	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Not applicable.
Other flammability	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	1.9
Solubility(ies)	Not available.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	Not available.
Explosive properties	Not explosive.
Oxidizing properties	Not available.
Other information	Not available.

10. Stability and reactivity

Reactivity	May polymerize. See the other subsections of this section for further details.
Stability	Stable at normal ambient temperatures and when used as recommended.
Possibility of hazardous reactions	Not known.
Conditions to avoid	Keep away from heat, sparks and open flame. Protect against direct sunlight.
Materials to avoid	Strong oxidizing agents.
Hazardous decomposition products	Heating may generate the following products: Toxic gases or vapors.

11. Toxicological information

Information on toxicological effects

Routes of exposure	See section 4. Skin , Eyes , Ingestion , Inhalation
<u>Acute toxicity - oral</u>	
Notes (oral LD₅₀)	Not available.
<u>Acute toxicity - dermal</u>	
Notes (dermal LD₅₀)	Not available.
<u>Acute toxicity - inhalation</u>	

ESTELITE Σ QUICK

Notes (inhalation LC₅₀)	Not available.
<u>Skin corrosion/irritation</u>	
Skin corrosion/irritation	Not available.
Animal data	Not available.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Not available.
<u>Respiratory sensitization</u>	
Respiratory sensitization	Not available.
<u>Skin sensitization</u>	
Skin sensitization	Sensitizing.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Not available.
Genotoxicity - in vivo	Not available.
<u>Carcinogenicity</u>	
Carcinogenicity	Based on available data the classification criteria are not met.
IARC carcinogenicity	Some of the ingredients are listed or exempt.
NTP carcinogenicity	Some of the ingredients are listed or exempt.
OSHA Carcinogenicity	None of the ingredients are listed.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Not available.
Reproductive toxicity - development	Not available.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Not available.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Not available.
<u>Aspiration hazard</u>	
Aspiration hazard	Not available.
<u>Toxicological information on ingredients.</u>	

2,6-DI-tert-BUTYL-p-CRESOL**Carcinogenicity**

IARC carcinogenicity	IARC Group 3 Not classifiable as to its carcinogenicity to humans.
NTP carcinogenicity	Reasonably anticipated to be a human carcinogen.
OSHA Carcinogenicity	Not listed.

TITANIUM DIOXIDE**Acute toxicity - inhalation**

ATE inhalation (dusts/mists mg/l)	1.5
--	-----

ESTELITE Σ QUICK

Carcinogenicity

IARC carcinogenicity IARC Group 2B Possibly carcinogenic to humans.

NTP carcinogenicity Reasonably anticipated to be a human carcinogen.

OSHA Carcinogenicity Not listed.

12. Ecological Information

Toxicity No data available.

Acute toxicity - fish Not available.

Acute toxicity - aquatic invertebrates Not available.

Acute toxicity - aquatic plants Not available.

Chronic toxicity - fish early life stage Not available.

Short term toxicity - embryo and sac fry stages Not available.

Chronic toxicity - aquatic invertebrates Not available.

Persistence and degradability

Persistence and degradability No data available.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient Not available.

Mobility in soil

Mobility No information available.

Other adverse effects

Other adverse effects Not known.

13. Disposal considerations

Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

14. Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, DOT).

UN Number

Not applicable.

UN No. (IMDG) N/A

UN No. (ICAO) N/A

UN No. (DOT) N/A

ESTELITE Σ QUICK**UN proper shipping name**

Not applicable.

Transport hazard class(es)

Not applicable.

IMDG Class Not applicable.**ICAO class/division** Not applicable.**Transport labels**

No transport warning sign required.

Packing group

Not applicable.

IMDG packing group Not applicable.**ICAO packing group** Not applicable.**Environmental hazards****Environmentally Hazardous Substance**

No.

Special precautions for user

Not applicable.

Transport in bulk according to Not applicable.**Annex II of MARPOL 73/78
and the IBC Code****15. Regulatory information****Regulatory Status** This Product is Hazardous under the OSHA Hazard Communication Standard.**Regulatory References** 29 CFR 1910. 1200(g) Federal Regulations (OSHA Standard).**US Federal Regulations****SARA (311/312) Hazard Categories**

Acute

US State Regulations**California Proposition 65 Carcinogens and Reproductive Toxins**

None of the ingredients are listed

California Directors List of Hazardous Substances*2,6-DI-tert-BUTYL-p-CRESOL**p-METHOXYPHENOL***Massachusetts "Right To Know" List***2,6-DI-tert-BUTYL-p-CRESOL**p-METHOXYPHENOL**TITANIUM DIOXIDE*

ESTELITE Σ QUICK**Rhode Island "Right To Know" List***2,6-DI-tert-BUTYL-p-CRESOL**p-METHOXYPHENOL**TITANIUM DIOXIDE***Minnesota "Right To Know" List***2,6-DI-tert-BUTYL-p-CRESOL**p-METHOXYPHENOL**TITANIUM DIOXIDE***New Jersey "Right To Know" List***2,6-DI-tert-BUTYL-p-CRESOL**p-METHOXYPHENOL**TITANIUM DIOXIDE***Pennsylvania "Right To Know" List***2,6-DI-tert-BUTYL-p-CRESOL**p-METHOXYPHENOL**TITANIUM DIOXIDE***16. Other information**

Training advice	Ensure operatives are trained to minimize exposure. Only trained personnel should use this material.
Revision comments	§15. Regulatory information amended
Revision date	4/10/2020
Revision	3
Hazard statements in full	H317 May cause an allergic skin reaction.

The information which is contained in this document is based on available data. However, as such has been obtained from various sources, including independent laboratories, it is given without warranty or representation that is complete, accurate and can be relied upon. Tokuyama Dental Corp. has not attempted to conceal in any way the deleterious aspects of the product listed herein, but makes no warranty as to such information.